

Technical



Battery Charger:	Class 2, Integrated Power Supply
Plug:	Plug Matches Local Requirements
Battery Type/Fit:	NiMH: 2 or 4 AA/HR6, 2 or 4 AAA/HR03
Typical Weight:	108 g
Input:	100-240V AC, 50-60 Hz
Output:	AA battery x2: Min 1550 mA AA battery x4: Min 775 mA AAA battery x2: Min 388 mA AAA battery x4: Min 775 mA
Operating Temp:	0°C – 35°C (32°F - 95°F)
Dimensions:	Open: 150 mm (L) x 50 mm (W) x 35 mm (H) Closed: 90 mm (L) x 50 mm (W) x 35 mm (H)

BENEFITS

Modern and Sleek design.
2 AA Ready in 45 minutes.*

FEATURES

Two Charging Channel

- 2 or 4 battery charging in combined slots (labeled)

Bi- Color Charging Status LED Indicator

- Red = Charging
- Green = Complete
- Flashing Red = Error/Abnormal battery or abnormal temperature

Fold to Close For Ultra Compact Design

International Charge Capability- device can be used worldwide with suitable converter plug

SAFETY

Microprocessor Controlled

- Charge Termination based on -dV/dt, temperature, and/or built in timer
- Primary battery protection- will not charge non-rechargeable batteries
- Over-temperature shut off- prevents overheat of battery
- Over-charge protection- prevents battery damage
- Low voltage battery protection- prevents overheat and damage to battery
- Power Protection Circuit- resets whenever battery is removed or power is interrupted

DURACELL®
BATTERIES

Berkshire Corporate Park
Bethel, CT 06801 U.S.A.
Tel: Toll free 1.800.544.5454
Web: www.Duracell.com

*Approx. 85% of full charge, when using Duracell AA1300 mAh NiMH Batteries.

Information and contents in this data sheet are for reference purposes only. They do not constitute any warranty and representation is subject to change without notice. For most current information and further details, please contact Duracell.